



PROJE NO:	GGOSB- Mİ T1 001	GGOSB
YAPAN		
KONTROL		Müşavir Firma PEGİ TEKNİK ENERJİ SİSTEMLERİ MÜH. MÜŞ. TAAH. LTD.ŞTİ.
ÖLÇEK (ÖLÇEKSİZ)	TARİH	

RMS-C EKİPMAN TABLOSU	
CAPACITY	:
INLET PRESSURE	: 3 - 4 Barg
OUTLET PRESSURE	: Barg
INLET-OUTLET VELOCITY	: 25 m/s (max.)

TEK HATLI TEK SAYACLI					
NO	MALZEME CİNSİ	MALZEME SINIFI	ADET	İLGİLİ ŞARTNAME	
1.0	WELDING NECK FLANGE / INLET	PN 40	1	TS 7005-1	
2.0	BALL VALVE STEEL BODY FULL BORE	PN 40	1	TS 9809	
3.0	PRESSURE GAUGE SCALE 0-6 bar GAS-M DIAL D.100 mm	PN 16 -40	1	DIN 16005	
3.1	BALL VALVE	PN 16 -40	5	TS 9809	
3.2	NEEDLE VALVE	PN 16 -40	1	TS 9809	
4.0	VENT VALVE	PN 16 -40	2	TS 9809	
5.0	CARTRIDGE FILTER - STEEL BODY	PN 16 -40	1	ASME VIII.1	
5.1	DIF.PRESSURE INDICATOR WITH CONTACT SWITCH + STEEL MANIFOLD	/	1	EN 10204 / 3.1.B	
5.2	DRAIN VALVE	PN 16 -40	1	TS 9809	
6.0	REGULATING ACTIV VALVE FLGD	PN 10 -16	2	DIN 3380	
7.0	SLAM SHUT VALVE - EXPROOF MICRO CONTACT SWITCH	/	2	DIN 3380	
8.0	PRESSURE GAUGE SCALE 0-4 bar - D.100 mm	/	2	DIN 16005	
9.0	PRESSURE SAFETY VALVE	PN 16 -40	1	DIN 3380	
9.1	BALL VALVE	PN 16 -40	1	TS 9809	
10.0	G - ROTARY METER WITH PULSE (LF) OUTPUT FOR SCADA CONNECTION	PN 16 -40	1	DIN- DVGW	
11.0	THERMOMETER SCALE - 30 / +60°C	/	1	DIN 16203	
13.0	BALL VALVE STEEL BODY FULL BORE	PN 16 -40	1	TS 9809	
14.0	WELDING NECK FLANGE (OUTLET)	PN 16 -40	1	TS 7005-1	
15.0	ALUMINYUM (2 mm) / STAINLESS STEEL CABINET	/	1	İMALATÇI ŞART	
17.0	EX-PROOF JUNCTION BOX	/	1	EN 50014/19/20	